

M-4010-400KV

Lipo	PROP	V	A	RPM	THRUST (g)
	TL2829 13*5.5	11.1	5.05	3995	600
3S	TL2830 14*5.5	11.1	6.61	3861	750
	TL2831 15*5.5	11.1	9.05	3635	1150
	TL2813 15*5.5	11.1	6.94	3852	900
	TL2834 15*7.5	11.1	6.2	3889	800
	TL2814 16*5.0	11.1	12.5	3376	1050
	TL2835 16*5.5	11.2	11.2	3497	1100
	TL2815 17*5.5	11.3	10.28	3613	1300
	TL2822 18*5.5	11.3	13.7	3327	1550
Lipo	PROP	V	A	RPM	THRUST (g)
4S	TL2828 12*5.5	14.9	5.78	5361	750
	TL2829 13*5.5	14.9	8.13	5114	850
	TL2830 14*5.5	14.9	10.57	4894	975
	TL2831 15*5.5	14.7	13.95	4516	1300
	TL2813 15*5.5	14.9	10.66	4894	1125
	TL2834 15*7.5	14.9	10.18	4919	1050
	TL2814 16*5.0	14.7	19	4063	1400
	TL2835 16*5.5	14.8	17.4	4274	1475
	TL2815 17*5.5	14.9	15.7	4416	1600
	TL2822 18*5.5	14.8	20.16	4052	1850
Lipo	PROP	V	A	RPM	THRUST (g)
5S	TL2828 12*5.5	18.6	8.3	6463	1100
	TL2829 13*5.5	18.5	11.97	6075	1500
	TL2830 14*5.5	18.6	15.45	5776	1850
	TL2831 15*5.5	18.5	20	5322	2250
	TL2813 15*5.5	18.5	14.9	5815	1950
	TL2834 15*7.5	18.5	14.6	5824	1900
	TL2814 16*5.0	18.4	28.4	4573	2100
	TL2835 16*5.5	18.5	24.4	4956	2250
	TL2815 17*5.5	18.5	22.02	5165	2550
	TL2822 18*5.5	18.4	27.18	4713	2950

Lipo	PROP	V	A	RPM	THRUST (g)
	TL2826 10*5.5	22.2	5.17	8150	825
6S	TL2827 11*5.5	22.3	8.6	7796	1200
	TL2828 12*5.5	22.2	11.4	7463	1500
	TL2829 13*5.5	22.2	16.22	6973	2000
	TL2830 14*5.5	22.2	20.84	6581	2450
	TL2831 15*5.5	22.2	26.7	6025	3000
	TL2813 15*5.5	22.3	19.7	6694	2550
	TL2834 15*7.5	22.2	19.6	6640	2500
	TL2815 17*5.5	22.2	29.1	5810	3300