



MII-4010-360KV



Lipo	PROP	V	A	RPM	TRUST (g)	Recommend flight weight(g)	Recommend flight weight(g)	Recommend flight weight(g)	Recommend flight weight(g)
3S	TL2830 14*5.5	11.13	4.34	3650	550	825	1100	1650	2200
	TL2831 15*5.5	11.1	6	3475	925	1387.5	1850	2775	3700
	TL2813 15*5.5	11.22	4.78	3600	675	1012.5	1350	2025	2700
	TL2834 15*7.5	11.11	4.45	3600	600	900	1200	1800	2400
	TL2814 16*5.0	11.12	8.83	3275	925	1387.5	1850	2775	3700
	TL2835 16*5.5	11.15	8.16	3325	925	1387.5	1850	2775	3700
	TL2815 17*5.5	11.11	7.48	3400	975	1462.5	1950	2925	3900
	TL2822 18*5.5	11.1	10.23	3175	1200	1800	2400	3600	4800
<b>Lipo</b>	<b>PROP</b>	<b>V</b>	<b>A</b>	<b>RPM</b>	<b>TRUST (g)</b>				
4S	TL2828 12*5.5	14.82	4	4925	525	787.5	1050	1575	2100
	TL2829 13*5.5	14.82	5.68	4775	850	1275	1700	2550	3400
	TL2830 14*5.5	17.85	7.19	4675	975	1462.5	1950	2925	3900
	TL2831 15*5.5	14.8	10	4400	1300	1950	2600	3900	5200
	TL2813 15*5.5	14.85	7.69	4600	1125	1687.5	2250	3375	4500
	TL2834 15*7.5	14.82	7.26	4625	1050	1575	2100	3150	4200
	TL2814 16*5.0	14.8	14	4100	1400	2100	2800	4200	5600
	TL2835 16*5.5	14.81	12.92	4175	1475	2212.5	2950	4425	5900
	TL2815 17*5.5	14.8	11.63	4275	1600	2400	3200	4800	6400
TL2822 18*5.5	14.85	15.75	3975	1850	2775	3700	5550	7400	
<b>Lipo</b>	<b>PROP</b>	<b>V</b>	<b>A</b>	<b>RPM</b>	<b>TRUST (g)</b>				
5S	TL2827 11*5.5	18.53	4.33	6150	600	900	1200	1800	2400
	TL2828 12*5.5	18.51	5.77	6000	850	1275	1700	2550	3400
	TL2829 13*5.5	18.52	8.39	5800	1225	1837.5	2450	3675	4900
	TL2830 14*5.5	18.55	10.75	5550	1450	2175	2900	4350	5800
	TL2831 15*5.5	18.5	14.87	5225	1900	2850	3800	5700	7600
	TL2813 15*5.5	18.53	10.86	5525	1625	2437.5	3250	4875	6500
	TL2834 15*7.5	18.53	10.7	5575	1550	2325	3100	4650	6200
	TL2814 16*5.0	18.5	21.05	4750	1950	2925	3900	5850	7800
	TL2835 16*5.5	18.54	19.21	4925	2075	3112.5	4150	6225	8300
	TL2815 17*5.5	18.5	16.78	5100	2275	3412.5	4550	6825	9100
TL2822 18*5.5	18.52	21.62	4675	2650	3975	5300	7950	10600	
<b>Lipo</b>	<b>PROP</b>	<b>V</b>	<b>A</b>	<b>RPM</b>	<b>TRUST (g)</b>				
6S	TL2826 10*5.5	22.32	3.72	7525	575	862.5	1150	1725	2300
	TL2827 11*5.5	22.27	6	7250	950	1425	1900	2850	3800
	TL2828 12*5.5	22.27	8.11	7050	1225	1837.5	2450	3675	4900
	TL2829 13*5.5	22.29	11.5	6750	1675	2512.5	3350	5025	6700
	TL2830 14*5.5	22.53	15.3	6475	2100	3150	4200	6300	8400
	TL2831 15*5.5	22.57	20.65	6050	2700	4050	5400	8100	10800
	TL2813 15*5.5	22.3	14.56	6450	2175	3262.5	4350	6525	8700
	TL2834 15*7.5	22.19	14.47	6425	2100	3150	4200	6300	8400
TL2815 17*5.5	22.13	22.02	5725	2925	4387.5	5850	8775	11700	