

MII-4015-340KV



Lipo	PROP	V	A	RPM	THRUST (g)	Recommend flight weight(g)	Recommend flight weight(g)	Recommend flight weight(g)	Recommend flight weight(g)
3S	TL2830 14*5.5	11.22	4.82	3700	650	975	1300	1950	2600
	TL2831 15*5.5	11.11	7	3575	900	1350	1800	2700	3600
	TL2813 15*5.5	11.12	5.18	3650	700	1050	1400	2100	2800
	TL2834 15*7.5	11.14	4.77	3675	625	937.5	1250	1875	2500
	TL2814 16*5.0	11.13	9.69	3400	975	1462.5	1950	2925	3900
	TL2835 16*5.5	11.13	9.01	3475	1000	1500	2000	3000	4000
	TL2815 17*5.5	11.12	8.06	3525	1075	1612.5	2150	3225	4300
	TL2822 18*5.5	11.11	11.33	3350	1350	2025	2700	4050	5400
Lipo	PROP	V	A	RPM	THRUST (g)				
4S	TL2828 12*5.5	14.81	4.08	4975	550	825	1100	1650	2200
	TL2829 13*5.5	14.81	6	4875	875	1312.5	1750	2625	3500
	TL2830 14*5.5	14.88	7.96	4775	1000	1500	2000	3000	4000
	TL2831 15*5.5	14.85	11.39	4550	1400	2100	2800	4200	5600
	TL2813 15*5.5	14.85	8.34	4725	1175	1762.5	2350	3525	4700
	TL2834 15*7.5	14.85	7.84	4775	1100	1650	2200	3300	4400
	TL2814 16*5.0	14.82	16.12	4325	1600	2400	3200	4800	6400
	TL2835 16*5.5	14.83	14.65	4400	1625	2437.5	3250	4875	6500
	TL2815 17*5.5	14.87	12.89	4475	1775	2662.5	3550	5325	7100
	TL2822 18*5.5	14.86	17.6	4275	2150	3225	4300	6450	8600
Lipo	PROP	V	A	RPM	THRUST (g)				
5S	TL2827 11*5.5	18.57	4.56	6225	675	1012.5	1350	2025	2700
	TL2828 12*5.5	18.55	6.29	6125	1875	2812.5	3750	5625	7500
	TL2829 13*5.5	18.58	8.98	5950	1225	1837.5	2450	3675	4900
	TL2830 14*5.5	18.5	11.98	5750	1575	2362.5	3150	4725	6300
	TL2831 15*5.5	18.5	16.92	5475	2200	3300	4400	6600	8800
	TL2813 15*5.5	18.57	11.98	5775	1775	2662.5	3550	5325	7100
	TL2834 15*7.5	18.52	11.47	5750	1650	2475	3300	4950	6600
	TL2814 16*5.0	18.5	24.66	5100	2250	3375	4500	6750	9000
	TL2835 16*5.5	18.56	21.77	5250	2350	3525	4700	7050	9400
	TL2815 17*5.5	18.58	19.17	5375	2600	3900	5200	7800	10400
TL2822 18*5.5	18.52	24.62	5100	3100	4650	6200	9300	12400	
Lipo	PROP	V	A	RPM	THRUST (g)				
6S	TL2826 10*5.5	22.7	3.8	7525	600	900	1200	1800	2400
	TL2827 11*5.5	22.24	6.25	7300	900	1350	1800	2700	3600
	TL2828 12*5.5	22.23	8.56	7175	1250	1875	2500	3750	5000
	TL2829 13*5.5	22.2	12.41	6925	1700	2550	3400	5100	6800
	TL2830 14*5.5	22.25	16.89	6700	2200	3300	4400	6600	8800
	TL2831 15*5.5	22.23	23.03	6325	2975	4462.5	5950	8925	11900
	TL2813 15*5.5	22.23	16.09	6725	2475	3712.5	4950	7425	9900
	TL2834 15*7.5	22.23	15.92	6675	2375	3562.5	4750	7125	9500
	TL2815 17*5.5	21.9	25.29	6150	3450	5175	6900	10350	13800
Lipo	PROP	V	A	RPM	THRUST (g)				
8S	TL2826 10*5.5	29.66	6.23	9775	1125	1687.5	2250	3375	4500
	TL2827 11*5.5	29.67	10.51	9375	1625	2437.5	3250	4875	6500
	TL2828 12*5.5	29.63	13.82	9025	2075	3112.5	4150	6225	8300
	TL2829 13*5.5	29.65	20	8550	2800	4200	5600	8400	11200
	TL2830 14*5.5	29.66	24.88	8025	3325	4987.5	6650	9975	13300
	TL2831 15*5.5	29.67	33.08	7425	4375	6562.5	8750	13125	17500
	TL2813 15*5.5	29.6	24.03	8250	3700	5550	7400	11100	14800
TL2834 15*7.5	29.64	24.21	8050	3650	5475	7300	10950	14600	