

Item.No	Prop	Volts	Amps(A)	RPM	Thrust(g)	Watts(W)	Efficiency(g/W)	Throttle
M-2205-2350KV	DAL 5040	11.1	4.46	14187	140	50	2.83	50%
		11.11	5.73	16273	175	64	2.75	65%
		11.1	6.56	17533	200	73	2.75	75%
		11.11	8.05	18601	250	89	2.80	85%
		11.11	10.23	20179	325	114	2.86	100%
	HQ 5045	11.11	5.22	12240	200	58	3.45	50%
		11.11	7.25	13834	250	81	3.10	65%
		11.11	9.54	15233	325	106	3.07	75%
		11.12	12.57	16950	400	140	2.86	85%
		11.11	15.72	18390	450	175	2.58	100%
	DAL 6040	11.11	5.38	11720	250	60	4.18	50%
		11.11	7.47	13142	300	83	3.61	65%
		11.11	10.19	14927	400	113	3.53	75%
		11.1	13.39	16331	500	149	3.36	85%
		11.11	17.14	17817	550	190	2.89	100%
	Prop	Volts	Amps(A)	RPM	Thrust(g)	Watts(W)	Efficiency(g/W)	Throttle
DAL 5040	14.81	6.65	18625	250	98	2.54	50%	
	14.81	8.32	20096	325	123	2.64	65%	
	14.81	10.26	21687	400	152	2.63	75%	
	14.8	12.94	23570	450	192	2.35	85%	
	14.81	10.23	20179	550	152	3.63	100%	
HQ 5045	14.8	7.77	15030	325	115	2.83	50%	
	14.8	11.36	17372	425	168	2.53	65%	
	14.81	13.9	18955	500	206	2.43	75%	
	14.81	18.37	20672	600	272	2.21	85%	
	14.83	23.17	22431	750	344	2.18	100%	
DAL 6040	14.81	7.94	14403	350	118	2.98	50%	
	14.8	11.85	16670	500	175	2.85	65%	
	14.8	15.66	18242	600	232	2.59	75%	
	14.82	19.87	19870	700	294	2.38	85%	
	14.82	25.22	21421	825	374	2.21	100%	